

Q12: 12,000 LB Capacity
ALI/ETL Certified 2-Post



AMERICAN Custom Lifts

POWDER COAT **FINISH**

Rubber protective door strip



Plated automatic arm restraints

Medium Duty 2-Post Lift Model: Q12

- ALI/ETL Certified
- Symmetric lifting capability
- Telescoping adapter pads
- Automatic arm restraints
- Single point lock release system
- Padded overhead shutoff system
- Adjustable Height

INSIDE COLUMNS

SPEED OF RISE **

MAX LOAD PER ARM

CEILING HEIGHT REQUIRED

MOTOR

VOLTAGE

Single push button power unit raises lift

(2921mm)

2 HP, SINGLE PHASE, 60Hz

208-230 13' 11" OR 14' 8""

(4470mm)

66 SECONDS

3000 LBS

(1360kg)



Single point mechanical. lock release system

Telescoping screw pads

Heavy Duty 2-stage front arms enable symmetric lifting capability

SPECIFICATIONS Model: Q12 12,000 (5443 kg) LIFTING CAPACITY (LBS.)* 78 1/8" RISF HFIGHT (1984mm) 13' 10" TO 14' 7" ADJ. HEIGHT OVERALL (4216mm or 4445mm) 11' 7 3/4" WIDTH OVERALL (3550mm) 103" DRIVE-THRU CLEARANCE (2616mm) 13' 3 ^{1/2"} TO 14' ^{1/2"} FLOOR TO OVERHEAD SWITCH (4051mm TO 4280mm) MIN. 35 3/4" MINIMUM ARM REACH (910mm) MAX. 54 1/2" MAXIMUM ARM REACH (1386mm) 5 1/4" TO 7 1/4" SCREW PAD HEIGHT (133mm TO 184mm) 115"

* Lift capacity ratings are based on loads equally distributed on all four arms. ** Lifting and lowering speeds may vary depending on the weight of the vehicle

OPTIONAL ACCESSORIES:

10315:

(4) 3" Stack Extensions, (2) 6" Stack Extensions and (2) Organizer Racks with hardware





10313: (2) 6" Stack Adapters Extensions

10314 (2) U-Shaped Frame Truck Adapters



10318:

(4) U-Shaped FrameTruck

